

Amendments to the Specification

Please replace paragraph 55 with the following, rewritten paragraph:

[0055] The described embodiments may be implemented as a method, apparatus or article of manufacture using programming and/or engineering techniques to produce software, firmware, hardware, or any combination thereof. The term “article of manufacture” and “circuitry” as used herein refers to a state machine, code or logic implemented in hardware logic (e.g., an integrated circuit chip, Programmable Gate Array (PGA), Application Specific Integrated Circuit (ASIC), etc.) or a computer readable medium, such as magnetic storage medium (e.g., hard disk drives, floppy disks,, tape, etc.), optical storage (CD-ROMs, optical disks, etc.), volatile and non-volatile memory devices (e.g., EEPROMs, ROMs, PROMs, RAMs, DRAMs, SRAMs, firmware, programmable logic, etc.). Code in the computer readable medium is accessed and executed by a processor. When the code or logic is executed by a processor, the circuitry may include the medium including the code or logic as well as the processor that executes the code loaded from the medium. ~~The code in which preferred embodiments are implemented may further be accessible through a transmission media or from a file server over a network. In such cases, the article of manufacture in which the code is implemented may comprise a transmission media, such as a network transmission line, wireless transmission media, signals propagating through space, radio waves, infrared signals, etc.~~ Thus, the “article of manufacture” may comprise the medium in which the code is embodied. Additionally, the “article of manufacture” may comprise a combination of hardware and software components in which the code is embodied, processed, and executed. Of course, those skilled in the art will recognize that many modifications may be made to this configuration, ~~and that the article of manufacture may comprise any information bearing medium known in the art.~~ Additionally, the devices, adapters, etc., may be implemented in one or more integrated circuits on the adapter or on the motherboard.